



### Request for Quote

Date Requested: \_\_\_\_\_

RFQ#: \_\_\_\_\_

**Representative Information:**

**Customer Information:**

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Contact: \_\_\_\_\_

Contact: \_\_\_\_\_

Phone: \_\_\_\_\_

Phone: \_\_\_\_\_

Fax: \_\_\_\_\_ E-mail: \_\_\_\_\_

Fax: \_\_\_\_\_ E-mail: \_\_\_\_\_

Material: \_\_\_\_\_

1. Qty.: \_\_\_\_\_ Sets  Plates

Plate Size Top: \_\_\_\_\_ X \_\_\_\_\_ X \_\_\_\_\_

Plate Size Bottom: \_\_\_\_\_ X \_\_\_\_\_ X \_\_\_\_\_

Panel size(s): (1) \_\_\_\_\_ X \_\_\_\_\_

(2) \_\_\_\_\_ X \_\_\_\_\_

(3) \_\_\_\_\_ X \_\_\_\_\_

(4) \_\_\_\_\_ X \_\_\_\_\_

Bushings: Installation: Recessed standard;   
Or: \_\_\_\_\_

Qty of Round \_\_\_\_\_ Inside Diameter: \_\_\_\_\_ Length .355  
or \_\_\_\_\_

Qty of Slotted \_\_\_\_\_ Size .1875 x .2500 standard Length .355 standard  
or; \_\_\_\_\_ X \_\_\_\_\_ or \_\_\_\_\_

Bushing Barrel Diameter .500 standard  
or \_\_\_\_\_

**Assessories:**

Pins; Slotted; \_\_\_\_\_ Length; \_\_\_\_\_ Round; \_\_\_\_\_ Length; \_\_\_\_\_

Bushings; Slotted; \_\_\_\_\_ Round; \_\_\_\_\_

Tuf-Lube 3-C \_\_\_\_\_ TL-2000 \_\_\_\_\_ DL- 1000 \_\_\_\_\_

Other; \_\_\_\_\_

**Special Instructions:**

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Thank you,  
Tadco, Inc.